

WEST·BOND. INC.



5400E – 5600E – 5700E SERIES

SEMI-AUTOMATIC WIRE BONDERS

Continuing a Tradition of Quality

5400E · 5600E · 5700E Series Semi-Automatic Bonders

545657E - Three-Way Convertibility, 45° Wire Feed, 90° Wire and Ribbon Feed, or Ball Bonder


5456E - Two-Way Convertibility, 45° Wire Feed, or 90° Wire and Ribbon Feed

5700E - Single Ball or Ball-Wedge Bonder



WEST-BOND'S Model 545657E brings forward the new advances of the "E" Series, notably the placement of all machine mechanism above the work plane to allow unlimited access, and the setting of axis brakes to lock on target. In this model the tool, rather than the work, is moved, both for alignment and for bonding, with the work pre-rotated. The machine bonds aluminum or gold wires ranging from 0.0007 in. to 0.002 in. and aluminum or gold ribbon ranging from 0.0005 in. x 0.002 in. to 0.001 in. x 0.010 in. Bonds are made by the wedge-wedge or ball-wedge technique using ultrasonic energy and work piece heat

CONVERTIBILITY for angled and vertical wire feed wedge bonding is easily accomplished with a simple change of clamping mechanisms, both of which are included with Model 5456E. Model 545657E expands convertibility with a tool head and Negative EFO assembly for single ball or ball-wedge bonding. All program variables and bond settings for each configuration are retained in memory between conversions.



PROGRAMMING for thirty different device types may be entered into separate buffers. Each device wire may have up to 21 stitch bonds with individual ultrasonic power, time, force, (high or low) and Z-Axes elevation control data. Program values, action prompts, and fault diagnostics are exhibited on the easy to read 4 lines, 40 characters LCD sequentially with machine operation.

ADDITIONAL FEATURES include 63 kHz ultrasonics (110Khz Available), orthogonal X-Y-Z axes with pure vertical Z, motion slaved Z encoder, pneumatic braking of X-Y-Z axes during bonding, and built-in tool heat. Available with the base and work platform for tabletop applications, or without base and work platform for mounting above any work handling system.



STANDARD SPECIFICATIONS

CONTROL LOGIC: Motorola 68000 microprocessor
MEMORY: 256KB RAM
DATA ENTRY: Keypad -12 keys
DISPLAY: 4 line, 40 character LCD
DEVICE STORAGE: Battery Backup RAM
TOOL Z STROKE: 0.5 inch
MOTORIZED Z RESOLUTION: 0.000208 inch per micro-step
MANUAL Z ENCODER RESOLUTION: 0.001 inch
FORCE RANGE: Adjustable, 10-250 grams,
BOND FORCE: High / Low Programmable
TRANSDUCER: ½ wave, 63 kHz (nominal)
ULTRASONICS: Built-in, 8 bit, 5 watts
ESD PROTECTION: Protection against Electrostatic Discharge

BALL FAULT DETECTION: Ball bonder
TAIL AND PULL STROKES: Programmable
ANGLED FEED TOOL LENGTH: 0.750 inch
VERTICAL FEED TOOL LENGTH: 0.750 inch
BALL CAPILLARY LENGTH: 0.625 inch
WIRE RANGE: 0.7 to 2 mils, ½ x10 mil gold ribbon (vertical feed)
WIRE SPOOL MOUNT: 0.5 inch with ball bearing roller
MICROMANIPULATOR: Counterbalanced, single lever X-Y-Z
RADIANT TOOL HEAT: Built-in
WORK PLATFORM: Fixed height. Adjustable height priced separately
MICROSCOPE: Selection available (ESD types available)
ILLUMINATOR: Selection available (ESD types available)
WORK HOLDERS: Selection available (ESD types available)

www.westbond.com

WEST·BOND·INC.
WEST·BOND INTERNATIONAL INC.

1551 Gene Autry Way Anaheim, California 92805, U.S.A.
Phone: (714) 978-1551
Fax: (714) 978-0431
E-mail: sales@westbond.com